



401 N. Raddant Rd.
 Batavia, IL 60510
 ph: 630-761-8900
 fx: 630-761-8989

Material Safety Data Sheet

Cyberlite U 334



1- Chemical Product and Company Identification:

Product Name: **Cyberlite U 334**
 Product Type: Ultraviolet Light Curing Adhesive
 Date revised: 10/6/10
 Emergency Number: 800-535-5053

2- Composition/Information on Ingredients:

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>%</u>
Isobornyl Acrylate	5888-33-5	15-20
Acrylate Oligomer	Trade Secret	30-50
Acrylic Acid	79-10-7	1-2
N,N-Dimethylacrylamide	2680-03-7	20-25

<u>Exposure Limits (TWA)</u>	<u>ACGIH (TLV)</u>	<u>OSHA (PEL)</u>	<u>OTHER</u>
Acrylic Acid	2 ppm	2 ppm	6 mg/m ³ (NIOSH)

<u>Exposure Limits (STEL)</u>			
Acrylic Acid	2 ppm	2 ppm	n/a

3- Hazards Identification:

Toxicity: Moderately toxic by ingestion.
 Eye, skin, and inhalation irritant.

Primary routes of Entry: Skin, inhalation, and eye contact

Signs of exposure: Irritation of eyes, skin, or respiratory tract.

Carcinogenic Ingredients:

NTP	None
IARC	None
OSHA	None

4- First Aid Measures:

Ingestion: Do not induce vomiting. Drink copious amounts of water and provide fresh air. Seek medical attention.

Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.

Skin contact: Wash with soap and water.

Eye contact: Flush with warm water. Seek medical attention.

5- Fire Fighting Measures:

Flash Point: not applicable

Extinguishing Media: Foam, Dry Chemical or Carbon Dioxide

Material Safety Data Sheet

Cyberlite U 334

Unusual Fire or Explosion Hazards: None.
Special Fire Fighting Procedures: Wear self-contained breathing apparatus.

6-Accidental Release Measures

Steps to be taken in case of spill or leak: Inform authorities in case of seepage into water system. Maintain adequate ventilation.

Soak up with inert absorbent. Store in a closed container until disposal.

7- Handling and Storage:

Safe storage: Store away from heat and direct sunlight to maximize shelf life. Store inside in a dry location between 50°F and 90°F.
Handling: Keep container tightly closed. Avoid contact with skin. Avoid breathing vapors.

8- Protective Equipment:

Ventilation: Local exhaust ventilation recommended for maintaining vapor level below TLV.
Respiratory protection: Not applicable with good local exhaust.
Skin: Neoprene or non-reactive gloves. Do not use cotton or wool.
Eye protection: Safety glasses or goggles with side shields.

9- Physical and Chemical Properties:

Appearance: clear liquid
Odor: Mild
Boiling Point: 212° F
Vapor Pressure: Less than .2mmHg @20C
Vapor Density: More than 1 (Air =1)
Evaporation rate: Not applicable
Specific Gravity: 1.1
Solubility in water: Negligible.
Auto Igniting: Product is not self-igniting

10- Stability and Reactivity

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: Photoreactive. Reacts with amines, acids, alkalis, and oxidizing agents.

Material Safety Data Sheet

Cyberlite U 334

11- Toxicological Information

Acute Toxicity: None
Primary Irritant affect: Irritant to skin, eye, and mucous membranes.
Sensitization: No sensitizing effects known.

12- Ecological Information

General Notes: Class 2 water hazard (self-assessment). Do not allow product to reach ground water or sewage system.

13- Disposal Considerations:

Spill or accidental release: Soak up with an inert absorbent.
Disposal procedures: Incinerate or dispose of in an approved landfill in accordance with local and EPA regulations. Not a RCRA hazardous waste.

14- Transportation Information:

Domestic Ground Transport:

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Marine pollutant: None

15- Regulatory Information

CA Proposition 65: No information

16- Other Information:

Hazard	NFPA Hazard Code®	HMIS Hazard Code®
Health	2	2
Fire	0	0
Reactivity	0	0
Specific Hazard	N/A	B

NFPA is a registered trademark of the National Fire Protection Association.

HMIS is a registered trademark of the National Paint and Coatings Association.

Prepared by: Cyberbond Regulatory Department
Company: Cyberbond L.L.C. • 401 North Raddant Road • Batavia, IL 60510
Phone: 630-761-8900 /Fax: 630-761-8989