



401 N. Raddant Rd.
 Batavia, IL 60510
 ph: 630-761-8900
 fx: 630-761-8989

Material Safety Data Sheet

Cyberpoxy 5895



1. Chemical Product and Company Identification:

Product Name: Cyberpoxy 5895 Part A
 Product Type: Epoxy Adhesive
 Revision Date: 7/10/10

2. Composition, Information on Ingredients:

Combination of non-hazardous materials.

<u>Hazardous component</u>	<u>CAS Number</u>
Bisphenol A (epichlorhydrin)	25068-38-6
Butyl Glycidyl Ether	2426-08-6
Ingredients which have exposure limits	

<u>Exposure limits (TWA)</u>	<u>ACGIH (TLV)</u>	<u>OSHA (PEL)</u>
Butyl Glycidyl Ether	25 ppm	25 ppm

3. Hazards Identification:

Toxicity:	Mild Eye Irritant.
Primary Routes of Entry:	Eye, skin contact.
Signs and symptoms of Exposure:	May cause dermatitis with prolonged contact on sensitive individuals.
Existing conditions aggravated by exposure:	None known.

4. First Aid Measures:

Ingestion:	Do not induce vomiting. Keep calm. Obtain medical attention.
Inhalation:	Does not apply.
Skin Contact:	Wash affected area with soap and water.
Eye Contact:	Flush with warm water for several minutes. Obtain medical attention.

5. Fire Fighting Measures:

Boiling Point	>400°F
Extinguishing Media:	Foam, Dry Chemical, or Carbon Dioxide

Material Safety Data Sheet

Cyberpoxy 5895

Unusual Fire or Explosion Hazards: None
Special Firefighting Procedures: None
Hazardous Products Formed by Fire Or Thermal Decomposition: Oxides of carbon; aldehydes and other organic substances may be formed during combustion.

6. Accidental Release Measures:

Steps to be taken in case of spill or leak: Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

7. Handling and Storage:

Safe storage: Store below 100°F.
Handling: Avoid contact with skin and eyes.

8. Protective Equipment:

Eye Protection: Safety glasses or goggles with side shields.
Skin: Rubber, polyethylene, or neoprene gloves.
Ventilation: Local exhaust preferred although good general mechanical ventilation is adequate except for confined areas.
Respiratory Protection: Does not apply.

9. Physical and Chemical Properties:

Appearance: White Paste
Odor: Mild
Boiling Point: > 400°F
Vapor Pressure: Less than 1mmHg @20°C
Vapor Density: Approximately 3 (air = 1)
Evaporation Rate: Not Applicable
Specific Gravity: 1.25
Solubility in Water: Negligible

10. Stability and Reactivity:

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: None

11. Toxicological Information: See Section 3

Material Safety Data Sheet

Cyberpoxy 5895

12. Ecological Information: No Data

13: Disposal Considerations:

Disposal Procedures: Incinerate or dispose of in an approved landfill in accordance with local and EPA regulations. Not a RCRA Hazardous waste.

14. Transportation Information:

Domestic Ground Transport

Proper Shipping Name: Unrestricted

Hazard Class or Division: Unrestricted

Identification Number: None

Marine Pollutant: No

15. Regulatory Information:

CA Proposition 65: This product contains saccharin. Proper usage necessitates no Proposition 65 warning.

16: Other Information:

Hazard	NFPA Hazard Code®	HMIS Hazard Code®
Health	3	3
Fire	1	1
Reactivity	1	1
Specific Hazard	None	Personal Protection See Section 8

NFPA is a registered trademark of the National Fire Protection Association.

HMIS is a registered trademark of the National Paint and Coatings Association.

Prepared by: Cyberbond Regulatory Department
Company: Cyberbond L.L.C. • 401 North Raddant Road • Batavia, IL 60510
Phone: 630-761-8900 /Fax: 630-761-8989

Material Safety Data Sheet

Cyberpoxy 5895

1. Chemical Product and Company Identification:

Product Name: Cyberpoxy 5895 Part B
Product Type: Epoxy Hardener
Revised: 7/10/10

2. Composition, Information on Ingredients:

<u>Hazardous component</u>	<u>CAS Number</u>
Polyamide resin	68082-29-1
Trithylenetetramine	112-24-3

This chemical has no documented exposure limits

3. Hazards Identification:

Toxicity:	Eye, skin, and respiratory irritant.
Primary Routes of Entry:	Eye, skin contact. Inhalation
Symptoms of acute over-exposure:	Prolonged contact may cause dermatitis with sensitive individuals. Can cause severe irritation with possible eye damage or blindness. Sensitization and delayed lung effects.

Existing conditions aggravated by exposure:

May aggravate existing skin, eye and lung conditions.

4. First Aid Measures:

Ingestion:	Do not induce vomiting. Administer 3-4 glasses of milk or water. Obtain immediate medical attention.
Inhalation:	Remove to fresh air. Administer oxygen if breathing is difficult. Get Medical attention if symptoms persist.
Skin Contact:	Remove contaminated clothing. Flush affected area with water for 15 minutes. Wash with soap and Water. Call physician if irritation develops.
Eye Contact:	Flush with warm water for 20 minutes. Obtain immediate medical attention.

Material Safety Data Sheet

Cyberpoxy 5895

5. Fire Fighting Measures:

Flash Point >200°F
Extinguishing Media: Foam, Dry Chemical, Water or Carbon Dioxide

Unusual Fire or Explosion Hazards: Personnel in vicinity and downwind should be evacuated.

Special Firefighting Procedures: Wear full bunker gear, self-contained breathing apparatus and protective clothing. Cool fire exposed containers with water.

Hazardous Products Formed by Fire Or Thermal Decomposition: Oxides of carbon, sulfur, and nitrogen; ammonia and other organic substances may be formed during combustion.

11. Accidental Release Measures:

Steps to be taken in case of spill or leak: Avoid personal contact. Soak up with inert absorbent. Store in a partly filled, closed container until disposal. Flush area with water to remove trace residue. Prevent spill from entering drainage/ sewer systems.

7. Handling and Storage:

Safe storage: Store below 100°F. Store in a cool, dry area away from high temperatures and flames.

Handling: Avoid contact with skin, eyes and clothing.

8. Protective Equipment:

Eye Protection: Safety glasses or goggles with side shields.

Skin: Chemical-resistant rubber gloves.

Ventilation: Local exhaust preferred although good general mechanical ventilation is adequate except for confined areas.

Respiratory Protection: None needed with normal use with proper ventilation. In areas of poor ventilation use NIOSH approved organic vapor cartridges for uncured resin.

Material Safety Data Sheet

Cyberpoxy 5895

9. Physical and Chemical Properties:

Appearance:	Black paste
Odor:	amine-like
Boiling Point:	Not determined
Vapor Pressure:	<1mmHg at 70°F
Vapor Density:	Not determined
Evaporation Rate:	Not determined
Specific Gravity:	1.28
Solubility in Water:	Negligible
VOC	0 g/L

12. Stability and Reactivity:

Stability:	Stable
Hazardous Polymerization:	Will not occur
Incompatibility:	Strong oxidizing agents and amines.

11. Toxicological Information: See Section 3

12. Ecological Information: No Data

13. Disposal Considerations:

Disposal Procedures: Incinerate or dispose of in an approved landfill in accordance with local and EPA regulations. Not a RCRA Hazardous waste.

14. Transportation Information:

Domestic Ground Transport
Proper Shipping Name: Non-regulated
Hazard Class or Division: N/A

Identification Number: N/A
Marine Pollutant: No

16. Regulatory Information:

CA Proposition 65: None

TSCA: All ingredients are listed or are exempt from listing.

SARA 312: Immediate health hazard; delayed health hazard

Material Safety Data Sheet

Cyberpoxy 5895

Canadian Regulations: WHMIS Hazard Class D2B

16: Other Information:

Hazard	NFPA Hazard Code®	HMIS Hazard Code®
Health	3	3
Fire	1	1
Reactivity	1	1
Specific Hazard	None	Personal Protection See Section 8

NFPA is a registered trademark of the National Fire Protection Association.

HMIS is a registered trademark of the National Paint and Coatings Association.

Prepared by: Cyberbond Regulatory Department
Company: Cyberbond L.L.C. • 401 North Raddant Road • Batavia, IL 60510
Phone: 630-761-8900 / Fax: 630-761-8989